AMERICAN JOURNAL OF AI CYBER COMPUTING MANAGEMENT
Peer Reviewed, Referred & Indexed Journal
E-ISSN:3069-0102
VOL.5, NO. 4(2025)

Deep Diabetic And Identification System Of Diabetic Eye Diseases Using Deep Neural Networks

[1]Kathroj Manasa,[2]Dr.V.Sudarshan

[1]MCA Student, Department Of Master of Computer Applications, Sri Chaitanya Institute Of Technology (Scit) Ponnekal ,Khammam

[1]Email : kathrojmanasa@gmail.com

[2]Professor, Department Of Master of Computer Applications, Sri Chaitanya Institute Of Technology (Scit) Ponnekal ,Khammam

[2]Email : sudharshan.cse@gmail.com

ABSTRACT

Diabetic retinopathy (DR) is a leading cause of vision impairment among diabetic patients. Early detection and timely treatment are crucial to prevent irreversible vision loss. This project introduces a comprehensive system leveraging deep neural networks, specifically Convolutional Neural Networks (CNNs), for the automated detection of diabetic eye diseases. The system comprises two primary modules: Admin and User. The Admin module facilitates dataset management, preprocessing, and model training, while the User module allows individuals to upload retinal images and receive diagnostic results. By integrating advanced deep learning techniques with user-friendly interfaces, this system aims to enhance the accuracy and efficiency of DR detection, thereby supporting healthcare professionals in early diagnosis and treatment planning.

Keywords: Diabetic Retinopathy, Convolutional Neural Networks,Automated Diagnosis.

I. INTRODUCTION

Diabetic retinopathy (DR) is a microvascular complication of diabetes mellitus that affects the retinal blood vessels, leading to vision impairment and potential blindness. The global rise in diabetes prevalence has consequently increased the incidence of DR, making it a significant public health concern. Early detection and treatment are paramount to prevent the progression of DR and preserve vision.

Traditional diagnostic methods involve manual examination of retinal images by ophthalmologists, which can be subjective and time-intensive. With advancements in medical imaging and machine learning, there is an opportunity to develop automated systems that can assist in the early detection of DR, thereby improving patient outcomes.

Deep learning, a subset of machine learning, has shown remarkable success in image recognition tasks. Convolutional Neural Networks (CNNs), in particular, have demonstrated high accuracy in medical image analysis, including DR detection. By training CNNs on large datasets of retinal images, these models can learn to identify patterns indicative of various stages of DR.

The proposed system integrates deep learning techniques into a user-friendly platform, enabling both healthcare professionals and patients to benefit from automated DR detection. The system comprises two modules: Admin and User. The Admin module allows for dataset management, preprocessing, and

model training, while the User module enables individuals to upload retinal images and receive diagnostic results.

In conclusion, the integration of deep learning into DR detection presents a promising avenue for enhancing diagnostic accuracy and efficiency. The proposed system leverages CNNs to provide an automated, reliable, and accessible solution for the early detection of diabetic eye diseases.

II. LITERATURE SURVEY

Diabetic Retinopathy Detection Through Deep Learning Using CNN Wide-Net-X Architecture

AUTHOR: Kavitha, T., Rohith, B., Lakha, A., & Chelikani, A.

ABSTRACT:
This study presents an advanced deep learning-based approach for the detection of diabetic retinopathy (DR) using the CNN Wide-Net-X architecture. The proposed system focuses on improving diagnostic accuracy by leveraging the capabilities of convolutional neural networks to automatically extract discriminative features from retinal fundus images. The methodology incorporates essential preprocessing steps such as image normalization, resizing, and noise reduction to enhance data quality and ensure consistent input for model training. The Wide-Net-X architecture is specifically designed to expand the network width, enabling it to capture more complex and subtle patterns in retinal images associated with different stages of DR.

Furthermore, the model is trained and validated on benchmark datasets to evaluate its classification performance across multiple severity levels of diabetic retinopathy. Experimental results demonstrate that the proposed approach achieves high accuracy, sensitivity, and specificity in detecting retinal abnormalities. The system effectively distinguishes between normal and diseased conditions, highlighting its robustness and reliability. This research emphasizes the potential of deep learning models in assisting ophthalmologists by providing automated, accurate, and early diagnosis, thereby contributing to improved patient care and reducing the risk of vision loss.

Diabetic Retinopathy Detection using Deep Learning

AUTHOR: Mane, D., Ashtagi, R., Jotrao, R., Bhise, P., Shinde, P., & Kadam, P.

ABSTRACT:
This research focuses on the application of deep learning techniques, particularly convolutional neural networks (CNNs), for the automated detection of diabetic retinopathy from retinal images. The study aims to design an efficient and reliable system that assists in early diagnosis by identifying pathological features present in fundus images. The methodology involves comprehensive preprocessing techniques such as image enhancement, normalization, and augmentation to improve the quality and diversity of the dataset. These steps help the model generalize better and perform effectively on unseen data.

The CNN model is trained and validated using standard datasets, and its performance is evaluated using various metrics such as accuracy, precision, recall, and F1-score. The results indicate that the proposed system achieves high accuracy and reliability in detecting diabetic retinopathy. The study highlights the effectiveness of deep learning in automating medical image analysis and reducing dependency on manual diagnosis. This approach demonstrates significant potential in improving clinical workflows and enabling faster and more accurate screening of diabetic retinopathy.

Computationally Efficient Deep Learning Models for Diabetic Retinopathy Detection: A Systematic Literature Review

AUTHOR: Khan, S. A., et al.

ABSTRACT:
This paper presents a comprehensive systematic literature review of computationally efficient deep

learning models used for diabetic retinopathy detection. The study examines various architectures, including convolutional neural networks, lightweight models, and optimization techniques aimed at improving performance while minimizing computational complexity. It analyzes different preprocessing methods, feature extraction strategies, and training approaches employed by researchers to enhance detection accuracy. The review provides a detailed comparison of models based on their efficiency, scalability, and suitability for real-world deployment.

In addition, the study highlights the strengths and limitations of existing approaches, identifying key challenges such as data imbalance, high computational cost, and lack of interpretability. The findings suggest that while deep learning models have achieved significant success in DR detection, there is a need for more efficient and resource-friendly solutions. This review serves as a valuable reference for future research, guiding the development of optimized models that can be effectively deployed in clinical environments for large-scale screening.

Using Deep Learning Architectures for Detection and Classification of Diabetic Retinopathy

AUTHOR: Mohanty, C., Mahapatra, S., Acharya, B., Kokkoras, F., Gerogiannis, V. C., Karamitsos, I., & Kanavos, A.

ABSTRACT:
This study explores the use of various deep learning architectures for the detection and classification of diabetic retinopathy. The research focuses on implementing convolutional neural networks to automate the analysis of retinal fundus images, enabling accurate identification of different DR stages. The methodology includes data preprocessing techniques such as image normalization and augmentation to improve model performance. Multiple deep learning architectures are evaluated to determine their effectiveness in capturing complex patterns associated with retinal abnormalities. The models are trained and tested on publicly available datasets, and their performance is evaluated using standard metrics such as accuracy and sensitivity. The results indicate that deep learning architectures can effectively classify diabetic retinopathy with high precision. The study highlights the potential of these models in clinical applications, providing a reliable tool for automated diagnosis and reducing the workload of healthcare professionals. It also emphasizes the importance of integrating deep learning into medical imaging systems for improved diagnostic outcomes.

III. EXISTING SYSTEM

The existing system for diabetic retinopathy detection primarily relies on manual examination of retinal fundus images by ophthalmologists. In conventional screening methods, specialists visually inspect retinal photographs to identify abnormalities such as microaneurysms, hemorrhages, exudates, and blood vessel changes. Although this approach is considered reliable when performed by experienced clinicians, it is time-consuming, labor-intensive, and highly dependent on the expertise of the examiner. In regions with limited healthcare resources, the shortage of trained ophthalmologists often results in delayed diagnosis and reduced screening coverage. Some semi-automated systems have been introduced to assist specialists by extracting handcrafted image features using traditional machine learning techniques. However, these systems require extensive feature engineering, struggle to generalize across diverse datasets, and often produce lower accuracy when detecting complex retinal abnormalities. Consequently, existing methods face challenges in scalability, consistency, and early detection, highlighting the need for more efficient and intelligent deep learning-based diagnostic systems.

IV. PROPOSED SYSTEM

The proposed system utilizes a Convolutional Neural Network (CNN) to automatically detect diabetic retinopathy from retinal fundus images with high accuracy and efficiency. The system begins by allowing the administrator to upload a labeled retinal image dataset, which is then preprocessed through resizing, normalization, noise reduction, and image



enhancement techniques to improve data quality. The processed images are used to train the CNN model, enabling it to learn complex retinal features associated with different stages of diabetic retinopathy. Once the model is trained, registered users can log into the system and upload a retinal image for analysis. The uploaded image undergoes the same preprocessing steps before being passed to the trained CNN model for prediction. The system automatically classifies the retinal image as healthy or diseased and identifies the severity of diabetic retinopathy, providing quick and reliable diagnostic support. This automated approach minimizes manual intervention, improves diagnostic consistency, reduces screening time, and assists healthcare professionals in the early detection and treatment of diabetic retinopathy.

V. SYSTEM ARCHITECTURE

The proposed System Architecture illustrates the complete workflow of a deep learning-based Diabetic Retinopathy Detection System. The architecture is divided into two major components: the Admin Module and the User Module. The admin is responsible for preparing and training the prediction model, while the user interacts with the trained system to upload retinal images and receive disease detection results. This separation ensures secure management of the dataset and provides an easy-to-use interface for end users.

The process begins with the Admin Login, where the administrator securely accesses the system using valid credentials. After successful authentication, the admin uploads the retinal fundus image dataset. The uploaded dataset serves as the foundation for model development and contains labeled images representing different stages of diabetic retinopathy. Restricting dataset management to the administrator maintains data integrity and prevents unauthorized modifications.

Once the dataset is uploaded, the system performs Image Preprocessing. During this stage, the retinal images are cleaned and standardized to improve their quality. Operations such as image resizing, normalization, contrast enhancement, noise removal, and pixel intensity adjustment are carried out to ensure that all images have a consistent format. Effective preprocessing reduces unnecessary variations in the dataset and improves the learning capability of the deep learning model.

After preprocessing, the system proceeds to the CNN Model Generation phase. The Convolutional Neural Network (CNN) is trained using the processed retinal images to automatically learn disease-related features such as microaneurysms, hemorrhages, and exudates. Through multiple training iterations, the CNN optimizes its internal parameters to accurately distinguish between healthy and diseased retinal images. Once training is completed, the generated model is stored and becomes available for prediction.

The User Module begins with the Registration process, where new users create an account by providing the required details.

After logging in, the user uploads a test retinal image through the prediction interface. The uploaded image undergoes the same preprocessing steps used during the training phase to maintain consistency between training and testing data. Finally, the CNN model identifies the presence and severity of diabetic retinopathy by analyzing the uploaded retinal image. The prediction result is displayed to the user, indicating whether the retina is healthy or affected by diabetic retinopathy and, if applicable, its stage. This automated prediction process assists healthcare professionals in early disease detection, reduces manual screening time, and improves diagnostic efficiency. After completing the task, both administrators and users can securely log out of the system, ensuring proper session management and data security.

AMERICAN JOURNAL OF AI CYBER COMPUTING MANAGEMENT
Peer Reviewed, Referred & Indexed Journal
E-ISSN:3069-0102
VOL.5, NO. 4(2025)




Fig 5.1: System Architecture

VI. IMPLEMENTATION




Fig 6.1: Admin Dashboard




Fig 6.2: Dataset Uploaded




Fig 6.3: Model Training




Fig 6.4: Uploading Test Image




Fig 6.5: Result Page

VII. CONCLUSION

The integration of deep neural networks into DR detection offers a promising solution to the challenges posed by traditional diagnostic methods. The proposed system automates the detection process, enhances accuracy, and provides accessible services to a broader population. By facilitating early detection and intervention, the system has the

potential to significantly reduce the incidence of vision loss due to diabetic eye diseases.

VIII. FUTURE SCOPE

Future enhancements to the system may include the integration of additional ocular disease detection capabilities, such as glaucoma and age-related macular degeneration. Incorporating real-time analytics and expanding the dataset to include diverse populations can further improve model accuracy and generalizability. Additionally, deploying the system on mobile platforms can increase accessibility, particularly in remote and underserved regions.

IX. REFERENCES

[1] S. P. Ting, L. Y. Cheung, G. Lim et al., "Development and Validation of a Deep Learning System for Diabetic Retinopathy and Related Eye Diseases Using Retinal Images from Multiethnic Populations with Diabetes," JAMA, vol. 318, no. 22, pp. 2211–2223, 2017.
DOI: https://doi.org/10.1001/jama.2017.18152

[2] V. Gulshan, L. Peng, M. Coram et al., "Development and Validation of a Deep Learning Algorithm for Detection of Diabetic Retinopathy in Retinal Fundus Photographs," JAMA, vol. 316, no. 22, pp. 2402–2410, 2016.
DOI: https://doi.org/10.1001/jama.2016.17216

[3] D. S. W. Ting, C. Y. L. Cheung, and T. Y. Wong, "Diabetic Retinopathy: Global Prevalence, Major Risk Factors, Screening Practices and Public Health Challenges," Diabetes Care, vol. 39, no. 4, pp. 567–576, 2016.
DOI: https://doi.org/10.2337/dc15-1239

[4] A. Abràmoff, M. K. Lavin, M. Birch, N. Shah, and J. C. Folk, "Pivotal Trial of an Autonomous AI-Based Diagnostic System for Detection of Diabetic Retinopathy," NPJ Digital Medicine, vol. 1, no. 39, 2018.
DOI: https://doi.org/10.1038/s41746-018-0040-6

[5] O. Russakovsky, J. Deng, H. Su et al., "ImageNet Large Scale Visual Recognition Challenge," International Journal of Computer Vision, vol. 115, no. 3, pp. 211–252, 2015.
DOI: https://doi.org/10.1007/s11263-015-0816-y

[6] K. He, X. Zhang, S. Ren, and J. Sun, "Deep Residual Learning for Image Recognition," Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR), 2016.
DOI: https://doi.org/10.1109/CVPR.2016.90

[7] C. Szegedy, W. Liu, Y. Jia et al., "Going Deeper with Convolutions," Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR), 2015.
DOI: https://doi.org/10.1109/CVPR.2015.7298594

[8] K. Simonyan and A. Zisserman, "Very Deep Convolutional Networks for Large-Scale Image Recognition," International Conference on Learning Representations (ICLR), 2015.
DOI (arXiv): https://doi.org/10.48550/arXiv.1409.1556

[9] F. Chollet, "Xception: Deep Learning with Depthwise Separable Convolutions," Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR), 2017.
DOI: https://doi.org/10.1109/CVPR.2017.195

[10] M. Tan and Q. Le, "EfficientNet: Rethinking Model Scaling for Convolutional Neural Networks," International Conference on Machine Learning (ICML), 2019.
DOI (arXiv): https://doi.org/10.48550/arXiv.1905.11946

[11] A. Krizhevsky, I. Sutskever, and G. E. Hinton, "ImageNet Classification with Deep Convolutional Neural Networks," Communications of the ACM, vol. 60, no. 6, pp. 84–90, 2017.
DOI: https://doi.org/10.1145/3065386

[12] I. Goodfellow, Y. Bengio, and A. Courville, Deep Learning. Cambridge, MA, USA: MIT Press, 2016.
DOI: https://doi.org/10.7551/mitpress/10243.001.0001

[13] D. P. Kingma and J. Ba, "Adam: A Method for Stochastic Optimization," International Conference on Learning Representations (ICLR), 2015.



DOI (arXiv): https://doi.org/10.48550/arXiv.1412.6980

[14] T. Pratt, M. M. Coenen, Y. Broadbent, S. Harding, and Y. Zheng, "Convolutional Neural Networks for Diabetic Retinopathy Detection," Procedia Computer Science, vol. 90, pp. 200–205, 2016.
DOI: https://doi.org/10.1016/j.procs.2016.07.014

[15] J. Krause, V. Gulshan, E. Rahimy et al., "Grader Variability and the Importance of Reference Standards for Evaluating Machine Learning Models for Diabetic Retinopathy," Ophthalmology, vol. 125, no. 8, pp. 1264–1272, 2018.
DOI: https://doi.org/10.1016/j.ophtha.2018.01.034

